













HRX SERIES Hydraulic Hammers



HYDRAULIC HAMMERS			HRX-25S	HRX-35S	HRX-55S	HRX-85S	HRX-125S	HRX-165S
	Excavator class ¹	t	1.0 - 2.5	2.0 - 4.5	4 - 7	6 - 8	7 - 14	12 - 19
	Weight	kg	130	170	360	450	640	1000
	Blows	bpm	700 - 1200	600 - 1100	500 - 900	400 - 800	400 - 800	350 - 700
	Working pressure	bar	120	120	140	150	160	170
	Oil flow	l/min	20 - 40	25 - 50	40 - 70	50 - 90	60 - 100	80 - 110
	Chisel diameter	mm	45	53	70	75	85	100

HYDRAULIC HAMMERS			HRX-225S	HRX-265S	HRX-325S	HRX-425S	HRX-525S
	Excavator class ¹	t	19 - 24	22 - 28	27 - 38	36 - 48	42 - 56
	Weight	kg	1730	2180	2940	3600	4400
	Blows	bpm	350 - 500	350 - 500	200 - 300	150 - 300	140 - 200
	Working pressure	bar	180	180	220	230	250
	Oil flow	l/min	120 - 150	120 - 180	180 - 240	200 - 260	220 - 270
	Chisel diameter	mm	135	140	155	165	175

¹ Recommended excavator / attachment combination