

















SSR SERIES Steel / Scrap shears



STEEL / SCRAP SHEARS			SSR-5R	SSR-8R	SSR-18R	SSR-28R	SSR-38R
	Excavator class ¹	t	4 - 7	6 - 10	12 - 20	20 - 28	32 - 42
	Weight	kg	420	580	1450	2520	3860
	Jaw opening	mm	200	305	390	510	610
	Jaw depth	mm	200	310	420	530	630
	Working pressure	bar	220	250	320	320	320
	Oilflow	l/min	60 - 80	80 - 100	120 - 150	180 - 220	200 - 250
	Working pressure rotation	bar	100	120	120	120	120
	Oilflow rotation	l/min	20	30	40	40	40

STEEL / SCRAP SHEARS			SSR-45R	SSR-52R	SSR-72R	SSR-84R
	Excavator class ¹	t	42 - 60	48 - 65	52 - 72	70 - 95
	Weight	kg	5740	6460	7120	9200
	Jaw opening	mm	670	710	820	925
	Jaw depth	mm	680	730	800	900
	Working pressure	bar	350	350	350	350
	Oilflow	l/min	220 - 280	260 - 320	280 - 360	300 - 400
	Working pressure rotation	bar	120	120	140	140
	Oilflow rotation	l/min	40	40	40	60

¹ Recommended excavator / attachment combination